




Demand more. Choose Foster

CPC2121 Commando Packaged Refrigerated Coldroom

CPC2121



Temperature

 Refrigerator 1/4 °C

Dimensions (mm)



| | W 2100 | D 2100 |
|--------|---|---|
| H 2100 |  |  |

Capacity

7.41 M³

Unpacked Weight

Features & Benefits

Foster Commando are available in Floored and Floorless options with 20 different sizes from 4m  to 10  ensuring you can have the perfect coldroom to suit your business

- Comes complete as a kit including panels, panel mounted refrigeration system, remote heat extraction system, shelving and installation kit
- Water-cooled heat removal system as standard on remote option - a 15% saving over traditional remote systems!
- Integrated panel-mounted refrigeration system; no complicated installation required
- Easy installation: 13amp single phase electrical supply on all models, and no drainage required!
- Lockable door (with internal safety release handle) and non-slip rigidised galvanised floor (on floored models) both offer safety in use

| External Finish | |
|-----------------|----------|
| White Foodsafe | Standard |
| Foodsafe | Standard |

| Internal Finish | |
|-----------------|----------|
| White Foodsafe | Standard |

| Shelving | |
|--------------------------|----------|
| Heavy Duty Nylon Racking | Standard |

| Doors | |
|---------------------|----------|
| Hinged - Right Hand | Standard |

| Refrigeration | |
|-----------------------|---|
| Forced Air | Standard |
| Integral | Standard |
| Remote Heat Exchnaged | Standard |
| Depth | Please allow 150mm to overall depth to allow for ref system and floor |
| Note: | |
| R404a | Standard |
| Drain Required? | No |

| Electrical Data & Service Information | |
|---------------------------------------|----------|
| 230 Volts | Standard |
| 50Hz | Standard |
| 1 Phase | Standard |
| Fuse Required (A) | P amp |

Footnotes

- PRV (pressure relief valve) supplied on all models as standard
- The standard position for the refrigeration system is on the left of the coldroom as shown in the diagrams. Right hand mounting (with left hand door hinging) is an option - please specify at the time of ordering
- Remote heat extraction system suitable for refrigerator and freezer temperatures.
- Remote heat extraction system supplied with 30m of pipe for connection (simple installation with the connection of two flexible pipes from unit to unit.
- Remote heat extraction unit can be mounted up to 5 metres vertically away from the compressor and up to 25 metres horizontally.
- Weather proof housing to the remote system means it is suitable for outdoor locations.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster