

Demand more. Choose Foster

CPC2418N Commando Packaged Refrigerated Coldroom CPC2418N



Temperature Refrigerator 1/4 °C			
Dimensions (mm)			
W 2400	D 1800		
H 2100			
Capacity			
7.24 M ³			
Unpacked Weight			

Features & Benefits

Foster Commando are available in Floored and Floorless options with 20 different sizes from $4m\frac{3}{3}$ to $10\frac{3}{3}$ ensuring you can have the perfect coldroom to suit your business

- Comes complete as a kit including panels, panel mounted refrigeration system, remote heat extraction system, shelving and installation kit
- Water-cooled heat removal system as standard on remote option a 15% saving over traditional remote systems!
- Integrated panel-mounted refrigeration system; no complicated installation required
- Easy installation: 13 amp single phase electrical supply on all models, and no drainage required!
- Lockable door (with internal safety release handle) and non-slip rigidised galvanised floor (on floored models) both offer safety in use

External Finish	
White Foodsafe	Standard
Foodsafe	Standard
Internal Finish	
White Foodsafe	Standard
Shelving	
Heavy	Standard
Duty	
Nylon	
Racking	

Doors				
Hinged - Right Hand		Standard		
Refrigeration				
Forced Air		Standard		
Integral		Standard		
Remote		Standard		
Heat Exchnaged				
Depth	Please allo	ow 150mm to		
Note:	overall depth to allow for			
	refsys	tem and floor		
R404a		Standard		
Drain		No		
Required?				

Electrical Data & Service Information		
230 Volts	Standard	
50Hz	Standard	
1 Phase	Standard	
Fuse Required (A)	P amp	

Footnotes

- PRV (pressure relief valve) supplied on all models as standard
- The standard position for the refrigeration system is on the left of the coldroom as shown in the diagrams. Right hand mounting (with left hand door hinging) is an option please specify at the time of ordering
- Remote heat extraction system suitable for refrigerator and freezer temperatures.
- Remote heat extraction system supplied with 30m of pipe for connection (simple installation with the connection of two flexible pipes from unit to unit.
- Remote heat extraction unit can be mounted up to 5 metres vertically away from the compressor and up to 25 metres horizontally.
- Weather proof housing to the remote system means it is suitable for outdoor locations.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com













150 14001



Demand more. Choose Foster