



Demand more. Choose Foster


## CPC2718 Commando Packaged Refrigerated Coldroom

# CPC2718





### Temperature

---

 Refrigerator 1/4 °C

### Dimensions (mm)

---

	W 2700	D 1800
H 2100		

### Capacity

---

8.20 M<sup>3</sup>

### Unpacked Weight

---

### Features & Benefits

---

Foster Commando are available in Floored and Floorless options with 20 different sizes from 4m<sup>2</sup> to 10<sup>2</sup> ensuring you can have the perfect coldroom to suit your business

- Comes complete as a kit including panels, panel mounted refrigeration system, remote heat extraction system, shelving and installation kit
- Water-cooled heat removal system as standard on remote option - a 15% saving over traditional remote systems!
- Integrated panel-mounted refrigeration system; no complicated installation required
- Easy installation: 13amp single phase electrical supply on all models, and no drainage required!
- Lockable door (with internal safety release handle) and non-slip rigidised galvanised floor (on floored models) both offer safety in use

External Finish	
White Foodsafe	Standard
Foodsafe	Standard

Internal Finish	
White Foodsafe	Standard

Shelving	
Heavy Duty Nylon Racking	Standard

Doors	
Hinged - Right Hand	Standard

Refrigeration	
Forced Air	Standard
Integral	Standard
Remote Heat Exchnaged	Standard
Depth	Please allow 150mm to overall depth to allow for ref system and floor
Note:	
R404a	Standard
Drain Required?	No

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Fuse Required (A)	P amp

## Footnotes

- PRV (pressure relief valve) supplied on all models as standard
- The standard position for the refrigeration system is on the left of the coldroom as shown in the diagrams. Right hand mounting (with left hand door hinging) is an option - please specify at the time of ordering
- Remote heat extraction system suitable for refrigerator and freezer temperatures.
- Remote heat extraction system supplied with 30m of pipe for connection (simple installation with the connection of two flexible pipes from unit to unit.
- Remote heat extraction unit can be mounted up to 5 metres vertically away from the compressor and up to 25 metres horizontally.
- Weather proof housing to the remote system means it is suitable for outdoor locations.

## Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: [sales@foster-uk.com](mailto:sales@foster-uk.com)

**FOSTER  
GREEN  
PROCUREMENT**



**Demand more. Choose Foster**