

Demand more. Choose Foster

Eco Pro G2 1/3 Meat/Chill Counter EP13M



Temperature



Dimensions (mm)

W 1865 D 700

Capacity

435 Litres

Unpacked Weight

124 KG

Features & Benefits

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

External Finish	
304 Stainless Steel	Standard
304 Stainless Steel Rear	Option
For Island Siting	

internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Shelving	
Additional Shelf	Option
Nylon Coated	Quantity: 6 Standard
Gastronorm	
1/1 Shelf	

Base Fittings	
80mm Castors	Standard
150mm Legs	Option
Levelling Bolts	Option

Doors	
Solid Full	Standard
Worktop & Drawers	
Temperature	
Worktop	Standard
100mm Splashback	Option
Less Worktop	Option

Refrigeration	
Forced Air	Standard
Integral	Standard
Remote - less condensing unit	Option
R290 (Hydrocarbon)	Option
R134a	Standard
Drain Required?	No

Electrical Data & Service Information	ce
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Running Watts	225
Running Amps	1.5
Thermal Heat Rejection (W)	235
Noise (dBa @ 1m)	TBC
Fuse Required (A)	10 amp

Product Extras		
Helicoil Mains Lead	Option	
Marine Kit	Option	
Width Reduction (178mm	Option	
reduction available when		
remote option selected)		

Footnotes

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Htz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: 0843 216 8800 Facsimile: 0843 216 4700 Email: sales@foster-uk.com















DENT HYDROCARBON LOW CARE

FULL SCOPE ISO 14001

OPE LOW PRODUCT I