

Demand more. Choose Foster

EcoPro G2 1350 Litre Upright Refrigerated Cabinet EP1440H



Temperature



Dimensions (mm)



Capacity

1350 Litres

Unpacked Weight

183 KG

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

External Finish	
304 Stainless Steel	Option
Stainless Steel	Standard
304 Stainless Steel Rear For Island Siting	Option

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Shelving	
GN 2/1 Shelf	Quantity: 6 Standard
Additional Shelf	Option

Base Fittings	
80mm Castors	Standard
150mm Legs	Option

Doors	
Solid Full	Standard
Solid Half	Option
Glass with Lights	Option
Refrigeration	

Refrigeration	
Forced Air	Standard
Integral	Standard
R290 (Hydrocarbon)	Option
R134a	Standard
Drain Required?	No

Electrical Data & Service Information		
230 Volts	Standard	
50Hz	Standard	
60Hz	Option	
1 Phase	Standard	
Running Watts	607	
Running Amps	4.4	
Thermal Heat Rejection (W)	627	
Noise (dBa @ 1m)	69.8	
Fuse Required (A)	10 amp	

Footnotes

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- Hydrocarbon option not available on glass door models
- 32 C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com













ISO 14001



LOW PRODUCT MILES

Demand more. Choose Foster