




Demand more. Choose Foster

## Eco Pro G2 2/3 Refrigerated Counter EP23H



### Temperature

---

 Refrigerator 1/4 °C

### Dimensions (mm)

---

W 2480      D 800  
H 865

### Capacity

---

760 Litres

### Unpacked Weight

---

163 KG

### Features & Benefits

---

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

External Finish		Doors		Electrical Data & Service Information	
304 Stainless Steel	Standard	Solid Full	Standard	230 Volts	Standard
304 Stainless Steel Rear For Island Siting	Option	Glass with Lights	Option	50Hz	Standard
Internal Finish		Worktop & Drawers		1 Phase	Standard
304 Stainless Steel	Option	<b>Temperature</b>		Running Watts	519
Aluminium	Standard			Running Amps	3.6
Shelving		Worktop	Standard	Thermal Heat Rejection (W)	539
GN 2/1 Shelf	Quantity: 6 Standard	100mm Splashback	Option	Noise (dBa @ 1m)	TBC
Additional Shelf	Option	Saladette Cut Out	Option	Fuse Required (A)	10 amp
Nylon Coated Gastronorm 1/1 Shelf	Option	Night Cover for Saladette Cutout	Option	Product Extras	
Base Fittings		Less Worktop	Option	Helicoil Mains Lead	Option
80mm Castors	Standard	1/2 Drawers	Option	Marine Kit	Option
150mm Legs	Option	1/3 Drawers	Option	Width Reduction (178mm reduction available when remote option selected)	Option
Levelling Bolts	Option	Refrigeration			
		Forced Air	Standard		
		Integral	Standard		
		Remote - less condensing unit	Option		
		R290 (Hydrocarbon)	Option		
		R134a	Standard		
		Drain Required?	No		

## Footnotes

- Where glass door option is requested please note that every door supplied is glass.
- Hydrocarbon option not available on glass door models
- Glass doors not available on 60Hz option
- 32oC ambient on glass door refrigerator model
- Any mix of two or three drawer units is possible, as is any combination of drawers and doors. Important - drawer sections are supplied without shelves. Will accommodate pans (optional extra): 1/2 drawers up to 150mm, 1/3 drawers up to 100mm (top drawer max. 70mm on 1/3 drawers).
- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.
- Depth with door open is 1418mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm

**FOSTER  
GREEN  
PROCUREMENT**



CORPORATE SOCIAL  
RESPONSIBILITY



INDEPENDENT  
VERIFICATION



HYDROCARBON  
REFRIGERANT



LOW CARBON



FULL SCOPE  
ISO 14001



LOW PRODUCT MILES

**Demand more. Choose Foster**