



Demand more. Choose Foster

EcoPro G2 600 Litre Upright Dual Temperature Refrigerated Cabinet

EP700HL



Temperature



Dual +1/+4 °C

Dimensions (mm)

W 700 D 865

H 2080



Capacity

600 Litres

Unpacked Weight

155 KG

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- Dual temperature option offers refrigerator and freezer temperatures in the same cabinet perfect when space is at a premium
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circularair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

| External Finish | | Doors | | Electrical Data & Service Information | |
|--|----------|---------------------|----------|---------------------------------------|----------|
| 304 Stainless Steel | Option | Solid Half | Standard | 230 Volts | Standard |
| Stainless Steel | Standard | Hinged - Right Hand | Standard | 50Hz | Standard |
| 304 Stainless Steel Rear For Island Siting | Option | Hinged - Left Hand | Option | 60Hz | Option |
| Internal Finish | | Refrigeration | | 1 Phase | Standard |
| 304 Stainless Steel | Option | Forced Air | Standard | Running Watts | 744 |
| Aluminium | Standard | Integral | Standard | Running Amps | 4.1 |
| | | R404a | Standard | Thermal Heat Rejection (W) | 754 |
| | | R134a | Standard | Noise (dBa @ 1m) | TBC |
| | | Drain Required? | No | Fuse Required (A) | 10 amp |
| Base Fittings | | | | | |
| 80mm Castors | Standard | | | | |
| 150mm Legs | Option | | | | |

Footnotes

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster