

# Demand more. Choose Foster


# EcoPro G2 600 Litre Upright Undermount Refrigerated Cabinet EP700HU



#### Temperature



### Dimensions (mm)



#### Capacity

600 Litres

## **Unpacked Weight**

121 KG

#### Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- Provides an alternative format for high ambients as it takes cooler air from floor level
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

External Finish			
304 Stainless Steel	Option		
Stainless Steel	Standard		
304 Stainless Steel Rear For Island Siting	Option		

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Shelving	
Additional Shelf	Option
GN 2/1 Shelf	Quantity: 3 Standard

Base Fittings	
80mm Castors	Option
150mm Legs	Option
Roller Castors	Standard

Doors		
Standard		
Standard		
Option		

Refrigeration			
Forced Air	Standard		
Integral	Standard		
R290 (Hydrocarbon)	Option		
R404a	Option		
R134a	Standard		
Drain Required?	No		

Electrical Data & Service Information	e
230 Volts	Standard
50Hz	Standard
60Hz	Option
1 Phase	Standard
Running Watts	305
Running Amps	2.0
Thermal Heat Rejection (W)	315
Noise (dBa @ 1m)	67.2
Fuse Required (A)	10 amp

#### Footnotes

- Optional castors supplied as standard increase overall height to 2070mm
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 150mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- Marine kit option includes legs, bulkhead brackets & marine shelves.

## Foster Refrigerator

Oldmedow Road - King's Lynn - Norfolk - PE30 4JU - United Kingdom Telephone: **0843 216 8800** Facsimile: **0843 216 4700** Email: sales@foster-uk.com















BON LOW CARBON

FULL SCOPE ISO 14001

LOW PRODUCT MLE